

Carrier Tape Forming Machine

Flexible, easy-to-use, advanced electronic characteristics make the CTFM-SH-18 a perfect choice for your forming needs

Features:

- Size L x W x H (cm): 300×60×166
- Weight (kg): 280kg
- Speed Meter/Hour: 260-360 meters/hour (depend on items)
- Forming Width (mm): 12-88mm
- Available Material: PS, PC, PET etc.
- Input reel diameter: ≤540mm
- Carrier tape thickness: 0.5mm
- Max Ko (mm) ≤22mm (Need custom for more depth KO)
- Output reel diameter: ≤600mm (single layer), for more layers need adding extra Cross Winding Machine
- Heating temperature: 0-300°C continuous adjustment
- Length of Transportation (mm): 40-112
- Power required: AC110/220V, 50-60HZ
- Air supply: 8.0kg/cm² 0.7±0.1kg/cm²
- Power Consumption: Max 2500W
- Environment temperature: -5°C~40°C

Main machine parameter

No.	Items	Brand	Series
1	PLC	Japan Mitsubishi	FX3GA
2	Touch screen	Taiwan Weinview	TK
3	Feeding motor	Chinese brand 锋铨	4GN
4	Rolling motor	Chinese brand 锋铨	4GN
5	Heating, Forming cylinder	Taiwai CHELIC	Double pole sliders
6	Other cylinders	Taiwai SHAKO	
7	Power	Taiwan Mingwei	350W
8	Solenoid valve	Janpan SMC	2 minute
9	Pull belt drive	Japan panasonic servo	Match Silver KK module

Photos

