


THE DIMENSIONS SHOWN ON THIS DESIGNED DRAWING ARE FOR ILLUSTRATIVE PURPOSE

DIMENSIONS FOR ACTUAL CARRIER TAPE MAY SLIGHTLY DIFFERENT

REV.	MODIFICATION	DATE	DRAWING	CHECKED	APPROVED
1					
2					



Not Marked tolerance $\pm 0.2\text{mm}$

D_0 E	D_1 E	P_0 A	P_2 A	E A						
$1.50^{+0.10}_{-0.00}$	$1.50^{+0.10}_{-0.00}$	4.00 ± 0.10	2.00 ± 0.10	1.75 ± 0.10						
ITEM	W E	A_0 A	A_1 A	B_0 A	B_1 A	K_0 C	K_1 C	P_1 A	F A	T E
DIM	12.00 ± 0.30	3.80 ± 0.10	± 0.10	3.80 ± 0.10	± 0.10	1.80 ± 0.10	± 0.10	8.00 ± 0.10	5.50 ± 0.10	0.30 ± 0.05
ALTERNATE										

- The Maximum cumulative tolerance is $\pm 0.2\text{mm}$ for 10 sprocket hole pitch
- Cambers do not exceed 1.0mm in 250mm length
- All dimension follow EIA-481-D series definition
- Material: PS black
- One 22" Reel=100 Meters

RoHS Compliance	NAME.	CARRIER TAPE	Mold Ref	QFN3.5X3.5	SIZE	A4	DSGD		DIM TOL	Ang Tol	
	Mold Ref	3.80*3.80*1.80	Customer P/N		SHEET	1/1	PROJ		$X \pm 0.30$	$X.XX \pm 0.10$	$X \pm 5'$
	MATERIAL	PS BLACK	SCALE	1:1	REV	A/0	CHKD		$X.X \pm 0.20$	$.XXX \pm 0.05$	$.XX \pm 1'$
			UNIT	MM	DATE	2021.10.4	APPD				